

This environmental declaration is formulated in accordance with Byggsektorns Kretsloppsråd (The Ecocycle Council for the Building Sector) and Sveff (Sveriges Färgfabrikanterers Förening – Swedish Paint Manufacturers' Association) guidelines for environmental declarations. The information is based on industry agreements, industry recommendations and applicable legislation

## Environmental declaration Paint products

Brand: Dalapro Fine

Environmental labelling: Yes  No  Type of labelling \_\_\_\_\_ Licence number \_\_\_\_\_  
Comments: \_\_\_\_\_

### Company information

Company name: Scanspac AB Telephone 1: +46 (0)19-46 34 00  
Corporate ID number: 5566354006 Telephone 2: \_\_\_\_\_  
Contact person: Anders Sakari Fax: +46 (0)19-46 57 31  
Street address: Kemivägen 7 E-mail: [info@dalapro.com](mailto:info@dalapro.com)  
Postal address: SE- 705 97 Glanshammar Website: [www.dalapro.se](http://www.dalapro.se)

<p><b>Environmental Policy</b></p> <p>Yes <input checked="" type="checkbox"/> No <input type="checkbox"/></p> <p>Comment: <u>Environmental work based on an overall view of the impact of the product throughout its service life</u></p>	<p><b>Environmental management system</b></p> <p>Yes <input checked="" type="checkbox"/> No <input type="checkbox"/></p> <p>Type: <u>ISO 14001</u></p> <p>Certified: <input checked="" type="checkbox"/> <input type="checkbox"/></p> <p>Registration number: <u>2007-SKM-AE-1214</u></p>
---	---

### Content declaration

Materials/substances Included	Type **	CAS-number	Environmental hazard*	Health danger*	Weight %
<i>Dolomite filler</i>	<i>F</i>	<i>16389-88-1</i>			<i>60-70</i>
<i>Light filler-perlite</i>	<i>F</i>	<i>93763-70-3</i>			<i>1-5</i>
<i>Water</i>	<i>S</i>	<i>7732-18-5</i>			<i>20-30</i>
<i>Copolymer dispersion</i>	<i>B</i>	<i>-</i>			<i>1-5</i>

\* According to the regulations and general advice of the National Chemical Inspectorate on classification and labelling, 1999:3 \*\* B=binder, P=pigment, F=filler, S=solvent, A=additive  
The solvents evaporate at the building stage and will no longer be present at the usage stage.

**Environmental impact (production stage)**

Energy type		Discharge into water	per kilo of product	Emission into the air	per kilo of product
Coal	%	COD	<1,4 mg/kg	CO <sub>2</sub>	No information*
Water	%	BOD	<0,3 mg/kg	CO	No information*
Oil	%	P	<0,1 µg/kg	SO <sub>x</sub>	No information*
Gas	%	N	<0,8 mg/kg	NO <sub>x</sub>	No information*
Electricity	100%	Heavy metals	<0,1 µg/kg	Dust	No information*
Biofuel	%			Ammonia	No information*
Own	%			VOC total**	No information*
	%				
Total use of energy ***	0,040				

\* Not relevant

\*\* Volatile organic substances

\*\*\* KWh per kilo produced product

**Raw material stage**

There is no information for raw materials.

**Source of raw materials/input goods**

	Scandinavia (%)	Rest of Europe (%)	Other (%)
Region of origin of the raw materials (Total for the manufacturing unit)	90	5	5

**Production stage**Does production generate residual products? Yes  No 

If yes, how are these dealt with:

Is any hazardous waste generated during production? Yes  No 

If yes, how is this dealt with:

EWC code: 08 04 10 Waste adhesives and sealants  
20 01 28 Paints, inks, adhesives and resins**Distribution of product****Production location and country** Glanshammar, SwedenMost common transport method (%): Truck 100% Ship Plane Train OtherForms of distribution Via warehouse:  Direct to customer Special forms of delivery Bulk:  Large packs:  One-off packages:  Other:**Packaging**Types of material used: PlasticREPA<sup>2</sup>- connection: Yes:  Customer no.: 9169312619 No:

If there is no REPA connection, specify how the producer responsibility is met:

---



---

**Building stage**

The product must be stored:

Frostproof

According to the Act (1988:868) on flammable & explosive goods

**Usage stage**

Operation / maintenance      The product requires no special input goods for operation and maintenance

Service length:                      Provided that the product has been applied in the manner stipulated by the manufacturer/supplier, the product can last as long as the base to which it is applied.

Emission

Type of emission	Amount of $\mu\text{g}/\text{m}^2 \text{ h}$			Measuring method
	4 weeks	26 weeks	..... weeks	
TVOC	<100			FLEC, SP1598

**Demolition/removal**

Does the item require special measures for protection of health and the environment?	Yes <input type="checkbox"/>	No <input checked="" type="checkbox"/>
--	------------------------------	--

If yes, specify how:

---



---



---

Cured product is handled as per the ordinance on hazardous waste      Yes       No

Non-cured product is handled as per the ordinance on hazardous waste      Yes       No

Is energy recovery possible for the product? \*      Yes       No

*\* Incineration should take place in controlled forms, e.g. in a combustion plant intended for the purpose..*

Other information:

---



---



---



---



---

<sup>2</sup> REPA = Register for Product Responsibility, cooperation between material companies.