

DALAPRO[®]

DESIGN

Water-based surface treatment that seals filled surfaces.
Produces a matt, wipeable surface.



Tip! View
instruction
film at
dalapro.com

Protects the filled surface against stains and dirt.

Produces a matt, wipeable surface.

Easy to apply with paint roller or pressure sprayer.

Quick-drying.



DALAPRO® DESIGN TOPCOAT

Water-based sealing of filled surfaces.

PRODUCT INFORMATION

Dalapro Design TopCoat is a water-based surface treatment that reinforces filled surfaces, making them more resistant to impact, scratching and moisture. After application, the filler retains its rustic appearance and any colour variations are emphasised.

APPLICATION

Used in combination with Dalapro Design and only in dry spaces indoors.

INSTRUCTIONS

Preparations: Remove dust from the surface to be treated. Cover the floor, mask skirting boards, door frames and, if necessary, cornices.

Step 1: Apply Dalapro Design TopCoat using a foam rubber roller or a short-bristled paint roller in a consistent, thin coating. Quickly dab clean any run-off using a cloth. Otherwise there is a risk that this will be visible in the finished job. Allow to dry.

Step 2: Repeat the application until you have achieved the desired end result. Normally requires at least two coats. If you want a stronger surface with a glossier finish, you can apply another coating of Dalapro TopCoat.

Dalapro TopCoat can also be applied with a pressure sprayer. In that case it should be diluted with 1 dl water per 5 dl Dalapro TopCoat. Recommended distance from wall: 30–40 cm. Make sure you have a good sprayer pattern before you start.

DRYING TIME

2–3 hours. At 20°C and 50% RH. The drying time is shorter at a higher temperature and lower RH, and longer for a lower temperature and higher RH.

APPLICATION TEMPERATURE

Both material and substrate must have a temperature of +10°C – +25°C.

MATERIAL CONSUMPTION

approximately 8 square metres per litre.

CLEANING AND DISPOSAL

Clean the tools with water. Residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Store in a dark, frost-free place (do not expose to sunlight). Unopened packaging can be stored for 12 months. Visit dalapro.com for more information.

TECHNICAL DATA

Solvent: Water

Viscosity: Slightly thixotropic

Dilution: Can be diluted with water if required.

pH: 7–8

Weight: 1 kilo per litre

Colour: Transparent

Flammability: Does not spread or support fire

Packaging: 1 litre



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com
Last amended 06/08/2020

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com