

DALAPRO[®]

FLEX

Flexible Caulk.



White flexible caulk.

For sealing gaps and crack in corners, around doors and windows.

Very good adhesion to most common substrates indoors and outdoors.

DALAPRO® FLEX

Flexible Caulk.

PRODUCT INFORMATION

Dalapro Flex is a flexible caulk for sealing gaps and cracks in corners and around doors and windows. Dalapro Flex has very good adhesion to most common substrates such as concrete, drywall, wood and bricks. When using outside, caulk must be painted.

WORKFLOW

Application on clean, dry and firm substrates using a caulking gun, down to +5C.

DRYING TIME

Open time 5-10 min, ready for paint after 30 min. Completely dry 1-7 days. Drying time depending of layer thickness, temperature and humidity.

CLEANING AND DISPOSAL

Remove as much caulk as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Store in frost free and avoid direct sunlight. Dalapro Flex is ready-to use and has a best before date. Unopened container can be stored up to 3 years.

TECHNICAL DATA

Binder: Acrylic

Solvent: Water

Aggregate: Calcium carbonate

Grain size: Max 0.2 mm

Dry content: Approx 53%

pH: Approx 8

Color: Offwhite

Filling capability: Good

Reaction to fire: Does not spread fire

Cleaning: Clean tools and waste with water

Packaging: Cartridge 300 ml



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com.

Last amended 12/08/2020

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com