

DALAPRO[®]

PREMIUM

Ready-mixed, white all-round hand filler.



High filling capacity.

Smooth consistency for easy application.

The white colour provides a good base for over-painting.

Suitable for joint filling on plasterboard.

DALAPRO[®] PREMIUM

Ready-mixed white, all-round hand filler.

PRODUCT INFORMATION

Dalapro Premium is a ready-mixed, all-round hand filler with high filling capacity. Suitable for filling holes and gaps, joint filling and smoothing. Suitable for use on most surfaces in new construction and renovation. Its special consistency makes it easy to work with. The filler is white, which provides a good base for over-painting with light colours.

USE

Suitable for installing paper tape. Combined with Scanspac Joint Tape, the product is suitable for joint filling on plasterboard. Meets CE-marking requirements in accordance with EN 13963. Manufactured in accordance with ISO 9001 and ISO 14001. When treating plasterboard: follow recommendations in accordance with EN 13963.

INSTRUCTIONS

Apply by hand to clean, dry and intact surfaces.
Temperature: minimum +5°C. Sand the filled surface down once it has dried. Use sandpaper with grain size 180-220. Eye and respiratory protection are recommended when sanding. Dust off before next treatment. Filled surfaces should be primed before wallpapering.

DRYING TIME

The drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

MATERIAL CONSUMPTION

For joint filling on plasterboard: approx. 0.3 litres/metre.
For thin smoothing with a 1 mm layer thickness: approximately 1 litre/square metre.

CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well.

Visit dalapro.com for more information.

TECHNICAL DATA

Binding agent: Latex co-polymer

Solvent: Water

Filler: Microspheres and white dolomite

Grain size: Max. 0.15 mm

pH: Approx. 9

Colour: White

Flammability: Does not spread or support fire

Packaging: 3-litre and 10-litre plastic buckets



Dalapro Premium is packaged in a bucket manufactured mostly of recycled plastic.



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com. Last amended 24/02/2026

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com