

DALAPRO[®]

ROLL JOINT

Ready-mixed roller filler with adhesive effect.
For joints and corners.



Ready-mixed, light grey roller filler for plasterboard joints and corner beads.

Adhesive effect provides optimal reinforcement
for paper tape and corner beads.

For plasterboard and concrete.

Roller filler saves time and is gentle on the back and shoulders.

Approved for installing paper tape.

Nordic Ecolabelled.

DALAPRO® ROLL JOINT

**Ready-mixed roller filler with adhesive effect.
For joints and corners.**

PRODUCT INFORMATION

Dalapro Roll Joint is a ready-mixed roller filler with adhesive effect. Specially adapted for joint filling with paper tape and corner reinforcements on plasterboard and concrete indoors. Not only does rolling of the filler save time, it is also ergonomic, causing less strain on the body. Light grey. Nordic Ecolabelled.

USE

Suitable for installing paper tape. Combined with Certain-Teed Marco Joint Tape, the product is suitable for joint filling on plasterboard. Meets CE-marking requirements in accordance with EN 13963. Manufactured in accordance with ISO 9001 and ISO 14001. When treating plasterboard: follow recommendations in accordance with EN 13963.

INSTRUCTIONS

Apply with a roller to clean, dry and intact surfaces. Temperature: minimum +5°C. Sand the filled surface down once it has dried. Use sandpaper with grain size 120–150. Eye and respiratory protection are recommended when sanding. Dust off before next treatment. Filled surfaces should be primed before wallpapering.

DRYING TIME

The drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

MATERIAL CONSUMPTION

For filling joints in plasterboard: approx. 0.3 litres/metre.

CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well.

Visit dalapro.com for more information.

TECHNICAL DATA

Binding agent: Latex co-polymer

Solvent: Water

Filler: Microspheres and white dolomite

Grain size: Max. 0.15 mm

pH: Approx. 9

Colour: Light grey

Flammability: Does not spread or support fire

Packaging: 12-litre plastic bucket



Dalapro Roll Joint is packaged in a bucket manufactured mostly of recycled plastic.



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com

Last amended 05/10/2023

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com