

# DALAPRO<sup>®</sup>

## S

Ready-mixed spray filler for new constructions and renovation.



**New formula – improved product qualities.**

**Good filling capacity.**

**High, consistent quality.**

**Suitable for walls and ceilings indoors.**

**For fine smoothing and texturing.**

**Suitable for big projects.**

**Nordic Ecolabelled, EPD-certified and IAC Gold.**

## DALAPRO<sup>®</sup> S

**Ready-mixed spray filler for new constructions and renovation**

### PRODUCT INFORMATION

Dalapro S is a traditional white, ready-mixed spray filler for use on all common types of indoor wall and ceiling surfaces. The product delivers consistently high quality and stable performance, every single time it is used. Contains dolomite marble of the highest quality, which provides a high level of whiteness and good filling capacity. Suitable for both fine smoothing and texturing in both renovation and new production. Nordic Ecolabelled.

### USE

Meets CE-marking requirements in accordance with EN 15824. Manufactured in accordance with ISO 9001 and ISO 14001. When finishing plasterboard: follow National guidelines.

### INSTRUCTIONS

Apply using spray application to clean, dry and intact surfaces. Temperature: minimum +5°C. Sand the filled surface down once it has dried. Use sandpaper with grain size 180-200. Eye and respiratory protection are recommended when sanding. Dust off before next application. Filled surfaces should be primed before wallpapering.

### DRYING TIME

The drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

### MATERIAL CONSUMPTION

For thin smoothing with a 1 mm layer thickness: approximately 1 litre/square metre.  
Spray-texturing approx. 0.3 litre/square metre.

### CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

### STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well. Visit [dalapro.com](http://dalapro.com) for more information.

### TECHNICAL DATA

**Binder:** Latex co-polymer

**Solvent:** Water

**Filler:** White dolomite

**Particle size:** Max: 0.3 mm

**pH: Approx.:** 9

**Colour:** White

**Flammability:** Does not spread or support fire

**Packaging:** 15 litre plastic bag



Dalapro S is packaged in a plastic bag manufactured from 30% recycled plastic.

This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at [www.dalapro.com](http://www.dalapro.com). Last amended 23/03/2026

Saint-Gobain Sweden AB, Scanspac  
Kemivägen 7  
SE-705 97 Glanshammar  
+46 (0)19-46 34 00  
[dalapro.com](http://dalapro.com)  
[info@dalapro.com](mailto:info@dalapro.com)