

- Manufactured from a special fibered-paper with added tensile strength to help prevent tearing, wrinkling or stretching.
- Marco Spark Perf is made with perforations, which help to prevent blistering.
- Spark-perforated for easy pass-through of air, eliminating air bubbles and reducing costly contractor callbacks
- Machine roughed for superior bonding and holding power.
- Precision-matched center-crease for easy and accurate corner applications.
- Designed for use with joint filler with EN13963 approval.



Product information

Marco Joint Tape is used to reinforce joints on gypsumboard on walls and ceilings.

Use

Marco Joint Tape is approved according to EN 13963. Always check National guidelines and regulations when finishing gypsumboards.

Workflow

1. Fill the tapered edge with Joint filler, 0.5 - 1.0 mm in the edge.
2. Embed Marco Joint Tape in the wet filler and use the knife to press the Marco Joint Tape in the filler.
3. After embedding, apply a thin layer of Joint Filler on the Marco Joint Tape, this is to really laminate the Joint tape into the Joint filler

Storage

Store in a dry place.

Technical Data

Roll length: 76 m / 23 m / 15 m

Width: Approx. 50 mm

Packaging: Carton of 20 rolls

Storage: Dry

Area of application: Indoors

This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are personally responsible for using the latest edition of this data sheet. Checks can be made at www.dalapro.com.

Last updated 18/10/2022