

DALAPRO[®]

AIRLESS S

A white spray filler for new construction and renovation



A white spray filler for new construction and renovation

For walls and ceilings indoors

For skimming and texturing

For the big projects

DALAPRO® AIRLESS S

Ready-mixed spray filler for new construction and renovation

PRODUCT INFORMATION

Dalapro Airless S is a traditional white, ready-mixed spray filler for airless application on all common types of indoor wall and ceiling surfaces. Fine dolomite marble provides maximum whiteness and build.

The product is suitable for thin smoothing and texturing in both renovation and new construction. The product fulfills CE marking requirements according to EN 15824 and is manufactured in accordance with ISO 9001 and ISO 14001.

Tools are to be cleaned in water. Large volumes of waste can be deposited as normal refuse at municipal refuse facilities. The plastic in the packaging is recyclable and must therefore be taken to the appropriate recycling point or municipal recycling plant.

INSTRUCTIONS

For spray application on clean, dry and firmly attached surfaces at a minimum temperature of +5°C. The filled surface is sanded when it has dried. Use sandpaper with particle size 100-120. Eye protection and a dust mask are recommended when sanding. Dust off before the next treatment. Filled surfaces should be primed before wall-papering.

CONSUMPTION OF MATERIAL

1 mm thin coat plastering = approx. 1 litre/m².

Spray-texturing = approx. 0.3 litre/m².

DRYING TIME

The drying time is dependent on substrate, layer thickness, temperature, air humidity etc.

STORAGE

Protect from frost and direct sunlight. Filler is perishable and therefore labelled with a date of production. Unopened packs can be stored for 12 months. Visit www.dalapro.com for further information.

TECHNICAL DATA

Binding agent: Latex co-polymer

Solvent: Water

Filler: White dolomite

Grain size: Max. 0.3 mm

pH: Approx. 9

Colour: White

Flammability: Does not spread or support fire

Packaging: 15 litre plastic bag



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com

Last amended 08/10/2018

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com