

# DALAPRO<sup>®</sup> WALLPAPER ADHESIVE

Wall adhesive for wallpapers.



A water-based starch adhesive for installation of paper wallpaper and wallpaper made of acrylic or vinyl with a paper reverse side.

Easy to apply.

Suitable for wall and ceiling surfaces indoors.

Suitable for both new production and renovation.

Apply the adhesive with a roller, spray, wallpapering machine or brush.

Nordic Ecolabelled.

## DALAPRO® WALLPAPER ADHESIVE

Wall adhesive for wallpapers.

### PRODUCT INFORMATION

Dalapro Wallpaper Adhesive is a transparent, Ecolabelled professional-quality wall adhesive. A water-based starch adhesive for installation of paper wallpaper and wallpaper made of acrylic or vinyl with a paper reverse side. Suitable for most substrates in new construction and renovation indoors.

### APPLICATION

The adhesive fulfils Swedish wallpaper industries trade organizations requirements for adhesive.

### INSTRUCTIONS

Substrates must be applied to clean, dry and intact surfaces at a temperature of at least +5 °C. Previously painted substrates must be clean, dry and sanded before applying the adhesive. For application, use a roller, brush, spray equipment or Tapofix.

### DRYING TIME

The drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

### MATERIAL CONSUMPTION

Approx. 0.2 litres/m<sup>2</sup>.

### CLEANING AND DISPOSAL

Remove as much adhesive as possible from the tools before cleaning them in water. Adhesive residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

### STORAGE

Adhesive has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well. Visit [dalapro.com](http://dalapro.com) for more information.

### TECHNICAL DATA

**Binding agent:** PVAc starch

**Solvent:** Water

**Density:** Approximately 1,000 kg/m<sup>3</sup>

**Dry matter content:** 6%

**Colour:** Transparent

**Flammability:** Does not spread or support fire

**Packaging:** 5-litre and 12-litre plastic buckets



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at [www.dalapro.com](http://www.dalapro.com).

Last amended 14/08/2019

Saint-Gobain Sweden AB, Scanspac  
Kemivägen 7  
SE-705 97 Glanshammar  
+46 (0)19-46 34 00  
[dalapro.com](http://dalapro.com)  
[info@dalapro.com](mailto:info@dalapro.com)