

DALAPRO[®]

LIGHTNING FACADE

Ready-mixed spray filler for repairs outdoors and indoors.



A grey filler for repairs on mineral surfaces.

Suitable for both indoors and outdoors.

Easy to work with.

DALAPRO® LIGHTNING NOVA

Ready-mixed spray filler for repairs outdoors and indoors.

PRODUCT INFORMATION

Dalapro Lightning Facade is a ready-mixed spray filler for repairs on walls and ceilings, outdoors and indoors on mineral surfaces. Grey.

USE

The product meets CE-marking requirements in accordance with EN 15824. Manufactured in accordance with ISO 9001 and ISO 14001.

INSTRUCTIONS

Apply using spray application to clean, dry and intact surfaces. Temperature: minimum +10°C. Sand the filled surface down once it has dried. Use sandpaper with grain size 100–120. Eye and respiratory protection are recommended when sanding. Dust off before next treatment. Filled surfaces must be primed before wallpapering.

DRYING TIME

Drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

MATERIAL CONSUMPTION

For thin smoothing with a 1 mm layer thickness: approximately 1 litre/square metre.

CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, above freezing, for up to 12 months. Containers that have been opened must be sealed well. Visit dalapro.com for more information.

TECHNICAL DATA

Binding agent: Latex co-polymer

Solvent: Water

Filler: Microspheres and white dolomite

Grain size: Max. 0.2 mm

pH: Approx. 9

Colour: Grey

Flammability: Does not propagate or support fire

Packaging: 15-litre plastic bucket



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com

Last amended 28/11/2019

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com