



PRODUCT DATA SHEET

Dalapro Lightning Facade



- A grey sprayfiller for skimming and patching on mineral substrates
 - Suitable for both indoor and outdoor use

Dalapro[®]



Dalapro Lightning Facade

A grey spray filler for skimming and patching on mineral substrates



PRODUCT INFORMATION

Dalapro Lightning Facade is a ready-mixed light weight spray filler for minor repairs outdoors (holes and cracks on mineral substrates) but can also be used for indoor plastering on most common substrates.

The filler is suitable for paper tape embedding according the requirements set in EN 13963. The product fulfills CE marking requirements according to EN 13963 and is manufactured in accordance with ISO 9001 and ISO 14001.

Tools are to be cleaned in water. Large volumes of waste can be deposited as normal refuse at municipal refuse facilities. The plastic in the packaging is recyclable and must therefore be taken to the appropriate recycling point or municipal recycling plant.

INSTRUCTIONS

Apply by spraying or by hand on clean, dry and firmly attached surfaces at a minimum temperature of +5° C. Use sandpaper, particle size 100-120, when sanding the dry surface. Eye protection and dust mask are recommended when sanding. Filled surfaces should be primed before wallpapering. Follow your local branch regulations and recommendations.

CONSUMPTION OF MATERIAL

Thin coat plastering = 1 litre/m² per mm

DRYING TIME

The drying time is dependent on substrate, layer thickness, temperature, air humidity etc.

STORAGE

Protect from frost and direct sunlight. Filler is perishable and therefore labelled with a date of production. Unopened packs can be stored for 12 months. Visit www.dalapro.com for further information.



TECHNICAL DATA

Binder: Latex co-polymer
Solvent: Water
Filler: Microspheres and white dolomite
Particle size: Max: 0.2 mm
Bulk density: Approx. 0.8 kg/litre
Vol: non-volatile matter Approx. 67%
pH: Approx. 9
Build: Very high (> 5 mm)
pH: Approx.: 9
Colour: Grey
Flammability: Does not spread or support fire
Packaging: 15 litre plastic bag

Dalapro product data sheets are provided for guidance only. The data presented does not constitute a guarantee that the product will have certain properties or be suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com.

Last updated 07/12/2017