

DALAPRO[®]

LIGHTNING MAX

Ecolabelled ready-mixed spray filler with extra high build.



A grey low shrinkage spray filler.

Suitable for walls and ceilings on all common substrates.

For new construction and renovation.

Provides a ready to paint surface.

For the big projects.

Nordic Ecolabelled.

DALAPRO® LIGHTNING MAX

Ecolabelled ready-mixed spray filler with extra high build.

PRODUCT INFORMATION

Dalapro Lightning Max is a grey, ready-mixed, coarse spray filler with a high build on all common types of indoor wall and ceiling surfaces. Dalapro Lightning Max is particularly suitable for filling where extra build is required. The product is suitable for initial filling and thin smoothing, in both renovation and new construction.

The product fulfills CE marking requirements according to EN 15824 and is manufactured in accordance with ISO 9001 and ISO 14001.

Tools are to be cleaned in water. Large volumes of waste can be deposited as normal refuse at municipal refuse facilities. The plastic in the packaging is recyclable and must therefore be taken to the appropriate recycling point or municipal recycling plant.

INSTRUCTIONS

For spray application or using a roller on clean, dry and firmly attached surfaces at a minimum temperature of +5°C. The filled surface is sanded when it has dried. Use sandpaper with particle size 100-120. Eye protection and a dust mask are recommended when sanding. Dust off before the next treatment. Filled surfaces should be primed before wallpapering.

MATERIAL CONSUMPTION

For thin smoothing with a 1 mm layer thickness: approximately 1 litre/square metre.

DRYING TIME

The drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well. Visit dalapro.com for more information.

TECHNICAL DATA

Binding agent: Latex co-polymer

Solvent: Water

Filler: Microspheres and white dolomite

Grain size: Max. 0.35 mm

pH: Approx. 9

Colour: Grey

Flammability: Does not spread or support fire

Packaging: 15-litre plastic bucket and 15-litre plastic sack



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com

Last amended 18/02/2019

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com