

DALAPRO[®]

MAX

Ecolabelled ready-mixed hand filler with high build.



A grey low shrinkage hand filler.

For walls and ceilings indoors.

For new construction and renovation.

Provides a surfaces ready for painting.

Nordic Ecolabelled.

DALAPRO[®] MAX

Ecolabelled ready-mixed hand filler with high build.

PRODUCT INFORMATION

Dalapro Max is a ready-mixed hand filler with extra high filling capacity. Suitable for initial filling and thin smoothing of walls and ceilings in new construction and renovation. Grey. Nordic Ecolabelled.

USE

Suitable for most substrates and produces a fine finish ready to paint. Meets CE-marking requirements in accordance with EN 15824. Manufactured in accordance with ISO 9001 and ISO 14001.

INSTRUCTIONS

Apply by hand to clean, dry and intact surfaces. Temperature: minimum +5°C. Sand the filled surface down once it has dried. Use sandpaper with grain size 100–120. Eye and respiratory protection are recommended when sanding. Dust off before next treatment. Filled surfaces should be primed before wallpapering.

DRYING TIME

The drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

MATERIAL CONSUMPTION

For thin smoothing with a 1 mm layer thickness: approximately 1 litre/square metre.

CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well. Visit dalapro.com for more information.

TECHNICAL DATA

Binding agent: Latex co-polymer

Solvent: Water

Filler: Microspheres and white dolomite

Grain size: Max. 0.35 mm

pH: Approx. 9

Colour: Grey

Flammability: Does not spread or support fire

Packaging: 3-litre and 10-litre plastic buckets



Dalapro Max 10 litre is packaged in a bucket manufactured in 100 % recyclable plastic and consists of at least 90 % recycled plastic.



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com

Last amended 07/06/2021

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com