

# DALAPRO<sup>®</sup>

# WOOD FINISH

Ready-mixed hand filler exclusively for woodwork.



A white, fine filler for woodwork.

For repairing and filling on doorframes, doors, cabinets etc. indoors.

Good adhesion and building properties.

Provides a ready-to-paint surface for woodwork and enamel paint.

## DALAPRO® WOOD FINISH

Ready-mixed hand filler exclusively for woodwork.

### PRODUCT INFORMATION

Dalapro Wood Finish is a ready-mixed, extra fine hand filler for woodwork. Use the product for filling frames, doors, hatches and suchlike indoors. Good adhesion, strength and building properties make the smoothed surface an excellent base coat for woodwork and enamel paint. White.

### USE

The product meets CE-marking requirements in accordance with EN 15824. Manufactured in accordance with ISO 9001 and ISO 14001.

### INSTRUCTIONS

Apply by hand to clean, dry and intact surfaces. Temperature: minimum +5°C. Sand the filled surface down once it has dried. Use sandpaper with grain size 100–120. Eye and respiratory protection are recommended when sanding. Dust off before next treatment. Filled surfaces must be primed before wallpapering.

### DRYING TIME

Drying time is dependent on factors such as substrate, layer thickness, temperature and humidity.

### MATERIAL CONSUMPTION

For thin smoothing with a 0.5 mm layer thickness: approximately 0.5 litre/square metre.

### CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

### STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, above freezing, for up to 12 months. Containers that have been opened must be sealed well. Visit [dalapro.com](http://dalapro.com) for more information.

### TECHNICAL DATA

**Binding agent:** Latex co-polymer

**Solvent:** Water

**Filler:** Microspheres and white dolomite

**Grain size:** Max. 0.03 mm

**pH:** Approx. 9

**Colour:** White

**Flammability:** Does not propagate or support fire

**Packaging:** 200 ml and 400 ml tubes, 500 ml and 3 litre plastic buckets



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at [www.dalapro.com](http://www.dalapro.com)

Last amended 22/11/2019

Saint-Gobain Sweden AB, Scanspac  
Kemivägen 7  
SE-705 97 Glanshammar  
+46 (0)19-46 34 00  
[dalapro.com](http://dalapro.com)  
[info@dalapro.com](mailto:info@dalapro.com)