



## PRODUCT DATA SHEET

# Dalapro DM60



- A white powder filler
  - 60 minute pot-life
- Does not shrink or crack
- For walls and ceilings indoors
- For new construction and renovation

**Dalapro**<sup>®</sup>



# Dalapro DM60

Multifunctional repair filler for concrete, plasterboard, fabric, renovation etc.



## PRODUCT INFORMATION

Dalapro DM60 is a white powder filler for repair filling and fine smoothing on all common types of indoor wall and ceiling surfaces. The powder is easy to mix to a smooth consistency and has an ideal drying time (around 60 minutes) for smoothing larger surfaces. The product is suitable in both renovation and new construction.

The product fulfills CE marking requirements and is manufactured in accordance with ISO 9001 and ISO 14001.

Tools are to be cleaned in water. Large volumes of waste can be deposited as normal refuse at municipal refuse facilities.

## INSTRUCTIONS

Apply by hand on clean, dry and firmly attached surfaces at a minimum temperature of +5 °C. Massive or non-absorbing surfaces should be dry, cleaned and primed. Try a minor surface in order to confirm good adhesiveness to the substrate. The filled surface is sanded when it has dried. Use sandpaper with particle size 100-120. Eye protection and a dust mask are recommended when sanding. Dust off before the next treatment. Filled surfaces should be primed before wallpapering.

## CONSUMPTION OF MATERIAL

1 mm thin coat plastering = approx. 0.9 kg/m<sup>2</sup>

## DRYING TIME

The drying time is dependent on substrate, layer thickness, temperature, air humidity etc.

## STORAGE

Protect from frost and direct sunlight. Filler is perishable and therefore labelled with a date of production. Unopened packs can be stored for 12 months. Visit [www.dalapro.com](http://www.dalapro.com) for further information.



## TECHNICAL DATA

Binder: Polymer-reinforced plaster  
Mixture: 1 part water – 2 parts powder (mix to desired consistency).  
Recommended layer thickness: 1–50 mm  
Open time: Ca 60 min  
Build: High. Minimum shrinkage  
Colour: White  
Flammability: Does not spread or support fire  
Packaging: Bag 12,5 kg

Dalapro product data sheets are provided for guidance only. The data presented does not constitute a guarantee that the product will have certain properties or be suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at [www.dalapro.com](http://www.dalapro.com)

Last updated 02-03-2017