

DALAPRO[®]

MAGNETIC

Ready mixed magnetic hand filler for drywall and concrete substrates.



A black tinted hand filler that provides a magnetic effect.

Perfect for a bulletin board at home, at the office or in other suitable areas.

Can be painted or varnished and still keep the magnetic effect.

Dalapro Magnetic do not effect wi-fi or any other electronic equipment.

Suitable for drywall or concrete substrates indoors.

Nordic Ecolabelled.

DALAPRO® MAGNETIC

Ready mixed hand filler for drywall and concrete substrates.

PRODUCT INFORMATION

Dalapro Magnetic is a surface filler that provides a magnetic effect. Suitable for all common substrates indoors. The smooth consistency makes it easy to spread the filler evenly over the substrate. Magnetic filler is perfect to create a bulletin board at home, at the office or in other suitable areas. Suitable for skimming in both renovation and new construction.

Dalapro Magnetic fulfills the CE- standard EN 15824 and is manufactured according to ISO 9001 and ISO 14001. Nordic Ecolabelled.

WORKFLOW

Dalapro Magnetic can be applied on clean, dry and firmly attached substrates with a minimum temperature of +5. When dry, use sandpaper 120-150 to sand the filler. Use a circular sanding motion to get the best result. When sanding use necessary protective equipment. Remove all dust before doing the next treatment.

The surface can be left unpainted, but if need for a harder surface it can be painted or varnished.

DRYING TIME

Drying time is dependent on layer thickness, temperature and humidity.

MATERIAL CONSUMPTION

Approximatley 3 liter / sqm. To get the best magnetic attraction a minimum of 3 mm must be applied.

CLEANING AND WASTE

Remove all waste material from tools before cleaning with water. All left over material can be left at the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be stored dark and free from frost for up to 12 months. Opened containers must be sealed properly. Visit dalapro.com for more information.

TECHNICAL DATA

Binding agent: Latex co-polymer

Solvent: Water

Filler: Microspheres and white dolomite

Grain size: Max 0.2 mm

pH: Approx 9

Colour: Black

Flammability: Does not spread or support fire

Packaging: 10 liter plastic bucket



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com

Last amended 02/03/2018

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com